Product Name	Fax2Email Server
Brief Description Fax2Email is a server to retrieve incoming fax. Faxes are sent out as email attachments in PNG format to selected recipients.	RS232 / LAN / DC power in (Front view) USB port x2 (Back view)
USB modem with fax line in & line out to fax machine USB flash (not included) Model no.	Use food Items in packaging FE-32
Certification	CE, FCC, LVD, RoHS compliant
Hardware/Firmware ver:	HFAX / F2E.xxxx
CPU / Flash / RAM	32-Bit RISC / 4MB / 16MB
Ports	2x USB, 1x RJ11(RS232), 1x RJ45(LAN), 1x DC Power Input
LCD Display	LAN IP address, No. of unsent e-mails, No. of fax received, No. of fax in errors, available storage (internal / USB flash), USB Wireless connected.
Server Size / Weight	48 x 63 x 22 mm / 75g (excluding USB modem)
Hardware Reset	Pin hole at bottom
Network Access	10/100 Base-T, RJ45 (Cat. 5)
Electrical Rating	Input: 5.3V 1A Output: DC5V, 500mA (for USB port)
Supported device	 USB Flash disk – for use to store incoming fax. Support FAT32 format. compatible USB Wireless – 802.11b/g dongle compatible USB Modem or Serial Modem (via RJ11 port) USB Hub – connect to increase USB ports NetFeeler Mini (via RJ11 port) – for temperature, humidity, RF smoke, RF door&window sensor.
Supported browser	IE and Java
Network Protocols	HTTP, PPPoE, TCP/IP, SMTP, Dynamic DNS, DNS Client, SNTP, DHCP.
Operating Environment	0°C ~ 60°C at 10% ~ 90% relative humidity. For indoor use only.
Packaging option	White Box / Bulk
Package dimension	180 x 150 x 60 mm
Net(Gross) weight/set	0.25kgw(0.35kgw) *subject to adaptor used
Carton measurement	790 x 390 x 340 mm (50 sets per standard carton)